



**MOBILE SYSTEMS INTEGRATORS**  
9726 E. 42<sup>nd</sup> St. Suite 233  
Tulsa, OK 74146  
918-665-8291 fax 918-664-8396

General Specifications: 8x12 Modular Equipment Shelter

---

Product or Services

---

Harford DuraCool Model No. 8X12X8 2,702 lbs total Class: 85  
Modular structure actual size 8' x 12' x 8' high, with one standard Harford entrance door 36" x 70".  
Ceiling panels to run as 4 x 6 with center I beam

1 8X12F-A Floor Panel, 14 gauge galvanized floor surface with OSB underlayment  
1 NOTE: Floor will support stationary loads - uniformly distributed - to 900# per sq. ft. (based on std. foot traffic & std. shelving) not recommended for cart traffic applications

40 Bottom of walls prepared with tapping plated 6 1/2" high per linear foot to work with attaching to skid

416 Interior Finish - 18 Gauge (.040) White Acrylic Aluminum Embossed Walls and Ceilings

320 Exterior Finish - 18 Gauge (.040) White Acrylic Aluminum Embossed Walls  
Exterior Finish (Ceilings) - 26 gauge galvanized

2 Door and Section to be Embossed White Aluminum in and out  
1 #1238 Pacesetter w/padlock provision & Hurd cylinder lock  
2 1277 Kason Hinges  
1 Tamper proof package hardware; security screws on door hardware,

Door Rain Shield, s/s, 42" x 9" deep  
117 Roof Cap - one piece, White Durolast, (membrane w/fastners, standard flashing) (40 mils), per sq. ft.  
32 Wall to foundation angle in a continuous band (24 ga. galvanized) mounting hardware by others, per linear ft.

GROUND SNOW LOAD @ PSF  
ROOF LIVE LOAD @ PSF  
Harford DuraCool Model No. LOADS BASED ON:  
Ground Snow Load @ 130 PSF  
Roof Live Load @ 100 PSF\*  
\*concentrated load of 200# centerline structure based on item on roof straddling the I Beam.  
Seismic Zone 4

Wind Loads 100

Electrical to include:

150 amp loadcenter with 12 breakers

4-4' 2 bulb fluorescent fixtures

4-duplex receptacles

1-light switch

exposed conduit

HVAC: Marvair 3-ton