



MOBILE SYSTEMS INTEGRATORS-TULSA

Quote Assistant

| | | | | | |
|---|------|--|--------------|--|---------------|
| Date: | | Date Req'd: | | | |
| Company: | | Contact: | | Project Reference/Location: | |
| Phone: | Fax: | | City: | State: | Zip: |
| Building End Use: | | | | | |
| Building Width (Inside Dimension): | | High Sidewall Ht: | Eave Height: | Clear Height Req'd: | |
| Building Length (Inside Dimension): | | Low Sidewall Ht: | | | Ship: |
| Building Siding Color: | | Building Trim Color: | | Building Door Color: | |
| Loadings: | | Roof: | | Liner Options: (flat,wht. metal) Gutter & Dn. Spouts: | |
| Snow Load: _____ psf | | <input type="checkbox"/> Shed Thickness: <input type="checkbox"/> 26 Ga. <input type="checkbox"/> 24 Ga. (std) Color: | | | |
| Wind Load: _____ psf | | <input type="checkbox"/> 1/2:12 Insulation: <input type="checkbox"/> 22 Ga. | | | |
| Floor Load: _____ psf | | <input type="checkbox"/> 2:12 Siding Options: (Ribbed Metal) | | | |
| Roof live Load: _____ psf | | <input type="checkbox"/> 4:12 <input type="checkbox"/> 26 Ga. <input type="checkbox"/> 24 Ga. <input type="checkbox"/> Plywood -size | | | |
| Seismic zone: _____ | | <input type="checkbox"/> 22 Ga. <input type="checkbox"/> Other (Specify) | | | |
| Walls: | | | | | Floor: |
| Thickness: (4" std) Exterior Walls: (24ga std) Interior Walls: (24ga std) | | | | | Loading: |
| <input type="checkbox"/> 26 Ga. <input type="checkbox"/> 24 Ga. <input type="checkbox"/> 26 Ga. <input type="checkbox"/> 24 Ga. | | | | | Material: |
| <input type="checkbox"/> 22 Ga. <input type="checkbox"/> 22 Ga. | | | | | Covering: |
| <input type="checkbox"/> Plywood -size Painted: | | | | | |
| Other Requirements (interior partition): <input type="checkbox"/> Other (Specify) | | | | | |
| Door (s): | | Door Hardware: | | Overhead Door Opening Size: | |
| Single - size: RH or LH Open: | | Door Lock: | | Roll-Up: | |
| Double - size: RH or LH Active: | | Panic Bar: | | Insulated: | |
| Thickness: Door Window Size: | | Hyd Closer: | | OverHead: | |
| Insulation: | | Door Stop: | | Insulated: | |
| | | Door Hasp: | | | |
| Other Requirements: | | | | | |
| Windows: | | Vents: | | Ridge Vent: | |
| Size: | | <input type="checkbox"/> Gravity Flow | | Length: | |
| Insulated: | | Intake Size: <input type="checkbox"/> Adjustable <input type="checkbox"/> Powered | | | |
| Other: | | Intake Shroud Filtered Intake <input type="checkbox"/> YES <input type="checkbox"/> NO | | 12" Turbine Vent | |
| | | Exhaust Size: | | | |
| Skylights: | | Exhaust Shroud: | | Other Requirements: <input type="checkbox"/> Installed | |
| Number Req'd: _____ | | | | <input type="checkbox"/> Not Installed | |
| Electrical: | | | | Special Options: | |
| Is this a hazardous location? <input type="checkbox"/> YES <input type="checkbox"/> NO | | | | Wave Guide Entry: | |
| Load Center: | | Lights Interior: | | Quantity: | |
| AC Volts: | | Lights Exterior: | | Size of Ports: | |
| Amps: | | Air Conditioner: | | Number of Ports: | |
| Phase: | | Btu's Req'd: | | Cable Tray: | |
| C.B.Slots: | | Vertical Mt. | | Width: | |
| C.B. 1-pole: | | Heat Strip: | | Length: | |
| C.B. 2-pole: | | Thru-Wall Mt: | | | |
| Other: | | Heater: | | Other: | |
| Duplex Receptacles: | | Btu's Req'd: | | | |
| Light Switches: | | Overhead Mt: | | | |
| | | Surge Arrestor: | | | |
| | | Rating: | | | |

MOBILE SYSTEMS INTEGRATORS
www.mobilesystemsintegrators.com
Larry Phillips

9726 E. 42nd St. Suite 233
918-665-8645 fax 918-664-8396

Tulsa, OK 74146

Attach sketch of building if necessary